

LISTING OF THE CLAIMS:

The following is a listing of claims (none of which are amended by this document):

1. (Previously Presented) A telecommunications network comprising a radio access network which generates and transmits, in a broadcast channel over an air interface, an access group eligibility message which enables a user equipment unit which receives the access group eligibility message to make a determination whether the user equipment unit is eligible to operate in a cell for which the access group eligibility message is transmitted, the determination involving a comparison of access group eligibility information transmitted in the access group message and an access group classification, the access group classification having been generated by a core network node which classified the user equipment unit into at least one of plural access groups.

2. (Original) The apparatus of claim 1, wherein the access group eligibility message indicates what subscriber groups are eligible to operate in the cell for which the access group eligibility message is transmitted.

3. (Original) The apparatus of claim 1, wherein the access group eligibility message indicates what restriction groups are not eligible to operate in the cell for which the access group eligibility message is transmitted.

4. (Original) The apparatus of claim 1, wherein the access group eligibility message includes a bitmap which indicates eligibility for plural access groups.

5. (Previously Presented) The apparatus of claim 1, wherein the core network node, upon receipt of a location update request for the user equipment unit, classifies the user equipment unit in the at least one of plural access groups and generates for transmission to the user equipment unit through the radio access network the access

group classification message which advises the user equipment unit as to which of the plural access groups the user equipment unit belongs.

6. (Previously Presented) The apparatus of claim 1, wherein the user equipment unit stores the access group classification obtained from the access group classification message in a memory at the user equipment unit.

7. (Original) The apparatus of claim 6, wherein the user equipment unit upon receiving the access group eligibility message compares the stored access group classification with contents of the access group eligibility message to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

8. (Original) The apparatus of claim 7, wherein the access group eligibility message includes a first bitmap which indicates eligibility for the plural access groups; wherein the access group classification message includes a second bitmap which advises the user equipment unit as to which of the plural access groups the user equipment unit belongs.

9. (Original) The apparatus of claim 8, wherein the user equipment unit performs a logical operation with respect to the first bitmap and the second bitmap to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

10. (Original) The apparatus of claim 9, wherein the first bitmap indicates which of plural subscriber groups are eligible and the second bitmap indicates to which one(s) of plural subscriber groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

11. (Original) The apparatus of claim 9, wherein the first bitmap indicates which of plural restriction groups are ineligible and the second bitmap indicates to which one(s)

of plural restriction groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

12. (Original) The apparatus of claim 7, wherein the user equipment unit is in one of an IDLE mode and one of the following states of a CONNECTED mode: CELL_FACH state; CELL_PCH state; and URA_PCH state.

13. (Original) The apparatus of claim 6, wherein upon entering a new cell which involves a transition to a new location area, the user equipment unit checks the access group eligibility message transmitted for the new cell in order to compare the stored access group classification with contents of the access group eligibility message to determine whether the user equipment unit is allowed access to the new cell.

14. (Original) The apparatus of claim 13, wherein upon entering a new cell which does not involve a transition to a new location area, the user equipment unit need not check the access group eligibility message to determine whether the user equipment unit is allowed access to the new cell.

15. (Original) The apparatus of claim 1, wherein the access group classification message is one of a location update response and a location update reject message which includes the access group classification.

16. (Original) The apparatus of claim 1, wherein the access group classification message is one of a location update response and a location update reject message which includes the access group classification and a version field associated with the access group classification.

17. (Original) The apparatus of claim 16, wherein upon receiving a subsequent core network message in the form of one of a location update response or location update reject message, the subsequent core network message including a potentially revised access group classification and a version field associated with the access group

classification carried by the subsequent core network message, the user equipment unit determines, by comparing contents of the version field associated with the access group classification and the version field associated with the access group classification carried by the subsequent core network message, whether the user equipment unit should update its stored access group classification.

18. (Original) The apparatus of claim 6, wherein the access group classification message generated by the core network includes the access group classification and a version field associated with the access group classification.

19. (Original) The apparatus of claim 18, wherein upon entering a new cell associated with a second core network, the user equipment unit receives an access group eligibility message transmitted for the new cell, the access group eligibility message transmitted for the new cell including a version field associated with the contents of the access group eligibility message transmitted for the new cell, and wherein the user equipment unit determines, by comparing contents of the version field associated with the access group classification and the version field associated with the access group eligibility message transmitted for the new cell, whether the user equipment unit should update its stored access group classification.

20. (CANCELED)

21. (CANCELED)

22. (CANCELED)

23. (CANCELED)

24. (CANCELED)

25. (CANCELED)

26. (CANCELED)

27. (CANCELED)

28. (CANCELED)

29. (CANCELED)

- 30. (CANCELED)
- 31. (CANCELED)
- 32. (CANCELED)
- 33. (CANCELED)
- 34. (CANCELED)
- 35. (CANCELED)
- 36. (CANCELED)
- 37. (CANCELED)
- 38. (CANCELED)
- 39. (CANCELED)
- 40. (CANCELED)
- 41. (CANCELED)

42. (Original) A user equipment unit which receives over an air interface an access group classification message and an access group eligibility message, the access group classification message being generated by a core network node for advising the user equipment unit as to which of the plural access groups the user equipment unit belongs, the access group eligibility message being generated by a radio access network node for specifying eligibility of plural access groups to operate in a cell for which the access group eligibility message is transmitted, the user equipment unit comprising:

an access controller which stores an access group classification obtained from the access group eligibility message and which compares the stored access group classification with contents of the access group eligibility message to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

43. (Original) The apparatus of claim 42, wherein the access group eligibility message indicates what subscriber groups are eligible to operate in the cell for which the access group eligibility message is transmitted.

44. (Original) The apparatus of claim 42, wherein the access group eligibility message indicates what restriction groups are not eligible to operate in the cell for which the access group eligibility message is transmitted.

45. (Original) The apparatus of claim 42, wherein the access group eligibility message includes a bitmap which indicates eligibility for plural access groups.

46. (Original) The apparatus of claim 45, wherein the access group eligibility message includes a first bitmap which indicates eligibility for the plural access groups; wherein the access group classification message includes a second bitmap which advises the user equipment unit as to which of the plural access groups the user equipment unit belongs.

47. (Original) The apparatus of claim 46, wherein the user equipment unit performs a logical operation with respect to the first bitmap and the second bitmap to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

48. (Original) The apparatus of claim 47, wherein the first bitmap indicates which of plural subscriber groups are eligible and the second bitmap indicates to which one(s) of plural subscriber groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

49. (Original) The apparatus of claim 47, wherein the first bitmap indicates which of plural restriction groups are ineligible and the second bitmap indicates to which one(s) of plural restriction groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

50. (Original) The apparatus of claim 42, wherein the access group classification message is one of a location update response and a location update reject message which includes the access group classification.

51. (Original) The apparatus of claim 42, wherein the access group classification message includes the access group classification and a version field associated with the access group classification.

52. (Original) The apparatus of claim 51, wherein upon receiving a subsequent core network message, the subsequent core network message including a potentially revised access group classification and a version field associated with the access group classification carried by the subsequent core network message, the access controller determines, by comparing contents of the version field associated with the access group classification and the version field associated with the access group classification carried by the subsequent core network message, whether the user equipment unit should update its stored access group classification.

53. (Original) The apparatus of claim 51, wherein upon entering a new cell associated with a second core network, the user equipment unit receives an access group eligibility message transmitted for the new cell, the access group eligibility message transmitted for the new cell including a version field associated with the contents of the access group eligibility message transmitted for the new cell, and wherein the access controller determines, by comparing contents of the version field associated with the access group classification and the version field associated with the access group eligibility message transmitted for the new cell, whether the user equipment unit should update its stored access group classification.

54. (Previously Presented) A method of operating a telecommunications network comprising:

transmitting, in a broadcast channel over an air interface, an access group eligibility message generated by a radio access network;

a user equipment unit which receives the access group eligibility message and which uses the access group eligibility message to make a determination whether the user equipment unit is eligible to operate in a cell for which the access group eligibility message is transmitted, involving a comparison of access group eligibility information transmitted in the access group message and an access group classification which is generated by a core network node.

55. (Original) The method of claim 54, further comprising including in the access group eligibility message an indication of what subscriber groups are eligible to operate in the cell for which the access group eligibility message is transmitted.

56. (Original) The method of claim 54, further comprising including in the access group eligibility message an indication of what restriction groups are not eligible to operate in the cell for which the access group eligibility message is transmitted.

57. (Original) The method of claim 54, further comprising including in the access group eligibility message a bitmap which indicates eligibility for plural access groups.

58. (Previously Presented) The method of claim 54, further comprising:
using a radio access network node to transmit the access group eligibility message;
at a core network node and upon receipt of a location update request for the user equipment unit, classifying the user equipment unit in at least one of plural access groups;

generating, for transmission to the user equipment unit through a radio access network, the access group classification message which advises the user equipment unit as to which of the plural access groups the user equipment unit belongs.

59. (Previously Presented) The method of claim 54, further comprising storing in a memory at the user equipment unit the access group classification obtained from the access group classification message.

60. (Original) The method of claim 59, further comprising the user equipment unit, upon receiving the access group eligibility message, comparing the stored access group classification with contents of the access group eligibility message to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

61. (Original) The method of claim 60, further comprising:
including in the access group eligibility message a first bitmap which indicates eligibility for the plural access groups; and
including in the access group classification message a second bitmap which advises the user equipment unit as to which of the plural access groups the user equipment unit belongs.

62. (Original) The method of claim 61, further comprising performing a logical operation with respect to the first bitmap and the second bitmap to determine whether the user equipment unit is allowed access to the cell for which the access group eligibility message is transmitted.

63. (Original) The method of claim 62, wherein the first bitmap indicates which of plural subscriber groups are eligible and the second bitmap indicates to which one(s) of plural subscriber groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

64. (Original) The method of claim 62, wherein the first bitmap indicates which of plural restriction groups are ineligible and the second bitmap indicates to which one(s) of plural restriction groups the user equipment unit belongs, and wherein the logical operation is a logical AND operation between corresponding bit positions of the first bitmap and the second bitmap.

65. (Original) The method of claim 54, wherein the user equipment unit is in one of an IDLE mode and one of the following states of a CONNECTED mode: CELL_FACH state; CELL_PCH state; and URA_PCH state.

66. (Original) The method of claim 54, further comprising:
upon the user equipment unit entering a new cell which involves a transition to a new location area, checking the access group eligibility message transmitted for the new cell; and
comparing the stored access group classification with contents of the access group eligibility message to determine whether the user equipment unit is allowed access to the new cell.

67. (Original) The method of claim 66, further comprising, upon the user equipment unit entering a new cell which does not involve a transition to a new location area, the user equipment unit not checking the access group eligibility message.

68. (Original) The method of claim 54, wherein the access group classification message is one of a location update response and a location update reject message which includes the access group classification.

69. (Original) The method of claim 54, further comprising including in the access group classification message the access group classification and a version field associated with the access group classification.

70. (Original) The method of claim 69, further comprising:
the user equipment unit receiving a subsequent core network message in the form of one of a location update response or location update reject message, the subsequent core network message including a potentially revised access group classification and a version field associated with the access group classification carried by the subsequent core network message;
the user equipment unit determining, by comparing contents of the version field associated with the access group classification and the version field associated with the

access group classification carried by the subsequent core network message, whether the user equipment unit should update its stored access group classification.

71. (Original) The method of claim 54, wherein the access group classification message generated by the core network includes the access group classification and a version field associated with the access group classification.

72. (Original) The method of claim 71, further comprising upon the user equipment unit entering a new cell associated with a second core network:

the user equipment unit receiving an access group eligibility message transmitted for the new cell, the access group eligibility message transmitted for the new cell including a version field associated with the contents of the access group eligibility message transmitted for the new cell; and

the user equipment unit determining, by comparing contents of the version field associated with the access group classification and the version field associated with the access group eligibility message transmitted for the new cell, whether the user equipment unit should update its stored access group classification.

73. (CANCELED)

74. (CANCELED)

75. (CANCELED)

76. (CANCELED)

77. (CANCELED)

78. (CANCELED)

79. (CANCELED)

80. (CANCELED)

81. (CANCELED)

82. (CANCELED)

83. (CANCELED)

84. (CANCELED)

85. (CANCELED)

86. (CANCELED)

87. (Previously Presented) The apparatus of claim 1, wherein the access group eligibility information comprises a subscriber group having a composition pre-agreed with a network operator.

88. (Previously Presented) The apparatus of claim 42, wherein the access group eligibility information comprises a subscriber group having a composition pre-agreed with a network operator.

89. (Previously Presented) The method of claim 54, wherein the access group eligibility information comprises a subscriber group having a composition pre-agreed with a network operator.